

FABRENE®

INDUSTRIAL SYNTHETIC FABRICS

TYPE FABRENE UDL®

Made from a polypropylene nonwoven, coated on two sides with polyethylene.

<u>PROPERTY</u>	<u>UNIT</u>		<u>VALUES</u>	<u>TEST METHOD</u>
Unit Weight	oz/yd ²		4.5	ASTM D3776
Tensile Grab Strength	lbf	Warp	105	ASTM D751
		Weft	79	
Tear Strength * (tongue)	lbf	Warp	9	ASTM D2261
		Weft	8	
Tear Strength (trapezoid)	lbf	Warp	24	ASTM D4533
		Weft	16	
Coating	mil	Grey	1.2	ASTM D1777 MOD
	mil	Grey	1.3	
Mullen Burst Strength	psi		118	ASTM D751
Vapour Perneance	Perms		1	ASTM E-96 Proc. A
Fastener Pull Resistance	lbs	Unaged	30.1	ASTM D3462
Nominal Thickness	mil		18	ASTM D1777 MOD

* Includes force to shift tapes - Tear may be crosswise to direction of force.

Fabrene UDL® contains some ultraviolet inhibitors and is suitable for short-term outdoor applications.
For further information, contact your FABRENE Inc. representative.

Suggested Applications: nonpermeable roofing membrane.

NOTE: These values are typical data and are not intended as limiting specifications.

Date: 07/07/06

SALES INQUIRIES

Fabrene Inc.
Tel: (888) 322-7363 ext 234
Tel: (705) 476-7057 ext 234
Fax: (705) 476-7787

ORDER DESK

North Bay, ON, Canada
Tel: (888) FABRENE
(888) 322-7363
ext. 222 or 226
Fax: (705) 476-0665

MAILING ADDRESS

Fabrene Inc.
240 Dupont Rd.
P.O. Box 4040
North Bay, ON, Canada
P1B 9B4

